

30<sup>m</sup> reserve on all expendables when "empty"

At on feedwater: final flag is out really empty -

but still have water in loop and ice on sublimator  
which will continue to cool.

but then will use up some of next charge filling sublimator  
lines and restarting at 0.3 lbs

For this reason water capability APOLLO 17

for EVA I is always slightly reduced.

but Sun angle is lower + so compensated - although work load higher.

PORTABLE LIFE SUPPORT SYSTEM (PLSS)

OXYGEN PURGE SYSTEM (OPS)

BUDDY SECONDARY LIFE SUPPORT SYSTEM (BSLSS)

BRIEFING

APOLLO 17

PLSS, OPS, BSLSS BRIEFING

I.	BASIC OPERATION	Page
	Primary Oxygen Subsystem	2
	Oxygen Ventilating Circuit	3
	Liquid Transport Loop	4
	Feedwater Loop	5
	EVCS/PLSS Interfaces	7
	→ Telemetry	
	Alarm System	
	Remote Control Unit	8
	Oxygen Purge System	9
	Buddy Secondary Life Support System	10
II.	CONFIGURATION DIFFERENCES	
	Apollo 14 vs. Apollo 15	11
	Summary	11
	Auxiliary Feedwater Reservoir	11
	Battery and Locking Mechanism	11
	Oxygen Supply	11
	LiOH Cartridge	12
	Hoses - Lengths and Routing	12
	Thermal Insulation	12
	Water Diverter Valve Change	12 (Ref. Pages 20 - 22)
	Recharge Procedure Change	13
	H <sub>2</sub> O Connector Alignment Marks	13
	RCU Dust Covers	14
	RCU Lower Hook Change	14
	OPS Mods for CMP EVA	14
	OPS Actuator Cable Length	14
	Weight Change	14
	Apollo 15 vs. Apollo 16	15
	Summary	15
	Connector Dust Covers	15
	O <sub>2</sub> Ground Charge Increase	15
	Feedwater Tanks Charged on Ground	15
	Recharge Procedure Change	15
	H <sub>2</sub> O Hose Length Change	16
	Antenna Protective Flap	16
	CDR Red Stripes on OPS	16
	Weight Change	16
III.	CONTROLS AND DISPLAYS	
	PLSS	17
	RCU	17
	OPS	18
	BSLSS	18
	CM EVA Hardware	19

IV.	RECHARGE PROCEDURES	Page
	Battery	
	LiOH Cartridge	
	Oxygen	
	Feedwater (Apollo 15 Procedure)	23
	(Apollo 16 Procedure)	24
V.	EVCS Operation	6